

EMT6144GK



ENGINEERING CODE
513306214



REFRIGERANT
R-404A



POWER SUPPLY
220-240 V 50 Hz



APPLICATION
MBP



MOTOR TYPE
CSIR



STANDARD
EN12900



COOLING CAPACITY
363 W



EFFICIENCY
1.82 W/W



DATA

GENERAL DATA

Model	EMT6144GK
Type	Hermetic Reciprocating
Technology	ON/OFF
Compressor Application	MBP
Expansion Device	Capillary Tube or Expansion Valve
Compressor Cooling	Fan/220
HP	1/4-
Starting Torque	HST
Plant	BRAZIL

ELECTRICAL DATA

Start Winding Resistance	21.1 Ω at 25°C
Run Winding Resistance	14.4 Ω at 25°C

MECHANICAL DATA

Displacement	3.97 cm³
Oil Charge	180 ml
Oil Type	ESTER
Oil Viscosity	ISO22
Weight	7.6 Kg

ELECTRICAL COMPONENTS

Start Capacitor	43-53 µf/330 V
CSR CSIR BOX	No
Starting Device Type	RELAY
Overload Protection	DRB170N61AXF

EXTERNAL CHARACTERISTICS

Base Plate	SMALL EUEM
Tray Holder	YES

Connector	Internal Diameter	Shape	Material
Suction	6.1 mm	SLANTED 42° UP + 45° TO BACK	COPPER
Discharge	4.94 mm	SLANTED PARALLET BP+24°TO BACK	COPPER
Process	6.1 mm	SLANTED 45° UP + 45° TO BACK	COPPER

PERFORMANCE

TESTED CONDITIONS

Tested Refrigerant	R-404A
Tested Application	MBP
Tested Standard	EN12900
Tested Cooling	Fan
Tested Voltage	220 V
Tested Frequency	50 Hz
Max Refrigerant Charge	250 g
Refrigerant Temperature	Dew

RATED POINTS

Condensing Temperature °C	Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
45	-10	363	1.82	200	-	10.91
Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.						

PERFORMANCE CURVE

Condensing Temperature 35°C

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-20	288	1.88	153	-	7.46
-15	356	2.15	165	-	9.32
-10	435	2.44	179	-	11.48
-5	527	2.75	191	-	14.03
0	632	3.13	202	-	17.04
5	751	3.60	209	-	20.56
10	885	4.23	210	-	24.69
Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.					

PERFORMANCE CURVE

Condensing Temperature 45°C


Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-20	237	1.39	170	-	6.98
-15	295	1.61	183	-	8.79
-10	363	1.82	200	-	10.91
-5	442	2.03	217	-	13.41
0	531	2.27	234	-	16.36
5	632	2.55	248	-	19.84
10	747	2.89	259	-	23.91
Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.					

PERFORMANCE CURVE

Condensing Temperature 55°C

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-10	289	1.38	209	-	10.24
-5	353	1.54	230	-	12.68
0	425	1.69	251	-	15.57
5	508	1.87	272	-	18.98
10	601	2.08	290	-	22.98
Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.					

ENVELOPE



EXTERNAL DIMENSIONS

