

INDICATORI DI UMIDITA' CON ATTACCHI DI RAME A SALDARE - OMOLOGATI DA UNDERWRITERS LABORATORIES INC.
 MOISTURE INDICATORS WITH COPPER BRAZE CONNECTIONS - APPROVED BY UNDERWRITERS LABORATORIES INC.
 VOYANT LIQUIDE AVEC INDICATEURS D' HUMIDITE AVEC RACCORDS A SOUDER EN CUIVRE - HOMOLOGUÉS PAR UNDERWRITERS LABORATORIES INC.
 FLÜSSIGKEITSINDIKATOREN MIT KUPFER LÖTANSCHLÜSSE - ZUGELASSEN VON UNDERWRITERS LABORATORIES INC.



Disegno Drawing Dessin Zeichnung	N° Catalogo Part Number N° Catalogue Katalog Nr	Attacchi Connections Raccords Anschlüsse			PS [bar]	MWP [psi] (1)	TS [°C]		Confezione n° pz Package pcs Emballage Verpackung
		SAE Flare	Ø ODS [in.]	Ø ODS [mm]			min.	max.	
	3940/2	-	1/4"	-	50	500	-40	+120	25
	3940/3		3/8"						
	3940/M10		-	10					
	3940/M12			12					
	3940/4		1/2"	-					16
	3940/5		5/8"	16					
	3940/M18		-	18					
	3940/6		3/4"	-					
	3940/7		7/8"	22					21
	3940/9		1.1/8"	-					16

| (1): in conformità a omologazione UL

| (1): according to UL approval

| (1): conformément à homologation UL

| (1): Übereinstimmung zur UL-Zulassung

INDICATORI D'UMIDITA' CON ATTACCHI DI RAME A SALDARE
 MOISTURE INDICATORS WITH COPPER BRAZE CONNECTIONS
 INDICATEURS D' HUMIDITE AVEC RACCORDS A SOUDER EN CUIVRE
 FLÜSSIGKEITSINDIKATOREN MIT KUPFER LÖTANSCHLÜSSE

Disegno Drawing Dessin Zeichnung	N° Catalogo Part Number N° Catalogue Katalog Nr	Attacchi Connections Raccords Anschlüsse							PS [bar]	TS [°C]		Confezione n° pz Package pcs Emballage Verpackung
		ODS		ODM		Per tubo For pipe Pour tuyau Für rohr				min.	max.	
		Ø [in.]	Ø [mm]	Ø [in.]	Ø [mm]	Ø [in.]	Ø [mm]	Foro Hole Orifice Loch				
								Ø [mm]				
	3770/M28	-	-	-	28	-	-	-	45	-30	+110	21
3770/11	1.3/8"			35								
	3770/13			1.5/8"								
	3770/M42		42									
	3771/11	1.3/8"	35	-	-	-	-	-	45	-30	+110	
3771/M42	-	42										
3771/17	2.1/8"	-										