

INDICATORI DI LIQUIDO CON ATTACCHI SAE FLARE MASCHIO - FEMMINA - OMOLOGATI DA UNDERWRITERS LABORATORIES INC.
 LIQUID INDICATORS WITH SAE FLARE MALE - FEMALE CONNECTIONS - APPROVED BY UNDERWRITERS LABORATORIES INC.
 VOYANTS DE LIQUIDE AVEC RACCORDS SAE FLARE MÂLE - FEMELLE - HOMOLOGUÉS PAR UNDERWRITERS LABORATORIES INC.
 FLUSSIGKEITSSCHAUGLAS MIT BÖRDELANSCHLÜSSE INNEN - AUSSEN- ZUGELASSEN VON UNDERWRITERS LABORATORIES INC.



Disegno Drawing Dessin Zeichnung	N° Catalogo Part Number N° Catalogue Katalog Nr	Attacchi Connections Raccords Anschlüsse			PS [bar]	MWP [psi] (1)	TS [°C]		Confezione n° pz Package pcs Emballage Verpackung
		SAE Flare	Ø ODS [in.]	Ø ODS [mm]			min.	max.	
	3850/22	1/4"	-	-	50	500	-40	+120	20
	3850/33	3/8"							
	3850/44	1/2"							
	3850/55	5/8"							
	3850/66	3/4"							16

| (1): in conformità a omologazione UL

| (1): according to UL approval

| (1): conformément à homologation UL

| (1): Übereinstimmung zur UL-Zulassung

INDICATORI DI LIQUIDO CON ATTACCHI DI RAME A SALDARE - OMOLOGATI DA UNDERWRITERS LABORATORIES INC.
 LIQUID INDICATORS WITH COPPER BRAZE CONNECTIONS - APPROVED BY UNDERWRITERS LABORATORIES INC.
 VOYANTS DE LIQUIDE AVEC RACCORDS A SOUDER EN CUIVRE - HOMOLOGUÉS PAR UNDERWRITERS LABORATORIES INC.
 FLUSSIGKEITSSCHAUGLAS MIT KUPFER LÖTANSCHLÜSSE - ZUGELASSEN VON UNDERWRITERS LABORATORIES INC.



Disegno Drawing Dessin Zeichnung	N° Catalogo Part Number N° Catalogue Katalog Nr	Attacchi Connections Raccords Anschlüsse			PS [bar]	MWP [psi] (1)	TS [°C]		Confezione n° pz Package pcs Emballage Verpackung
		SAE Flare	Ø ODS [in.]	Ø ODS [mm]			min.	max.	
	3840/2	-	1/4"	-	50	500	-40	+120	25
	3840/3		3/8"						
	3840/M10		-	10					
	3840/M12			12					
	3840/4		1/2"	-					16
	3840/5		5/8"	16					
	3840/M18		-	18					
	3840/6		3/4"	-					
	3840/7		7/8"	22					21
	3840/9		1.1/8"	-					16

| (1): in conformità a omologazione UL

| (1): according to UL approval

| (1): conformément à homologation UL

| (1): Übereinstimmung zur UL-Zulassung