


VALVOLE DI RITEGNO ERMETICHE A SQUADRA CON ATTACCHI ODS DI RAME - OMOLOGATE DA UNDERWRITERS LABORATORIES INC.

HERMETIC RIGHT ANGLE CHECK VALVES WITH COPPER ODS CONNECTIONS - APPROVED BY UNDERWRITERS LABORATORIES INC.

CLAPETS ANTI-RETOUR HERMÉTIQUES ANGLE DROIT AVEC CONNEXION CUIVRE ODS - HOMOLOGUÉS PAR UNDERWRITERS LABORATORIES INC.

HERMETISCHE RÜCKSCHLAGVENTILE WINKELANSCHLUSS MIT LÖTANSCHLUSS IN KUPFERAUSFÜHRUNG
ZUGELASSEN VON UNDERWRITERS LABORATORIES INC.



Disegno Drawing Dessin Zeichnung	N° Catalogo Part Number N° Catalogue Katalog Nr	Attacchi Connections Raccords Anschlüsse			Kv [m³/h]	Pressione differenziale Differential pressure Pression différentielle Differenzial Druck	PS [bar]	MWP [psi] (1)	TS [°C]		Confezione n° pz Package pcs Emballage Verpackung
		SAE Flare	ODS			(2)			Min	Max	
			Ø [in.]	Ø [mm]		[bar]					
	3184W/7	-	7/8"	22	9	0,04	50	600	-40	+150	14
	3184W/M28		-	28	19						1
	3184W/9		1.1/8"	-			45				
	3184W/11		1.3/8"	35	29	0,3					50
	3185W/7		7/8"	22	9		19				
	3185W/M28		-	28	45						
	3185W/9		1.1/8"	-							1
	3185W/11		1.3/8"	35	29						

(1): in conformità a omologazione UL
(2): minima pressione a cui la valvola è completamente aperta

(1): according to UL approval
(2): minimum pressure at which the valve is completely open.

(1): conformément à homologation UL
(2): pression minimum à laquelle le clapet est complètement ouvert

(1): Übereinstimmung zur UL-Zulassung
(2): minimaler Druck, bei dem das Ventil vollständig geöffnet ist

REGOLATORI DI CAPACITA' - OMOLOGATI DA UNDERWRITERS LABORATORIES INC.

HOT GAS BYPASS CAPACITY REGULATORS - APPROVED BY UNDERWRITERS LABORATORIES INC.

RÉGULATEURS DE CAPACITÉ - HOMOLOGUÉS PAR UNDERWRITERS LABORATORIES INC.

LEISTUNGSREGLER - ZUGELASSEN VON UNDERWRITERS LABORATORIES INC



Disegno Drawing Dessin Zeichnung	N° Catalogo Part Number N° Catalogue Katalog Nr.	Attacchi Connections Raccords Anschlüsse			Campo di regolazione Regulation range Plage de régulation Regelbereich	Kv [m³/h]	PS [bar]	MWP [psi] (1)	TS [°C]		Confezione n° pz Package pcs Emballage Verpackung
		SAE Flare	Ø ODS [in.]	Ø ODS [mm]					min.	max.	
	3310/4	1/2"	-	-	0,2 - 6	0,7	28	405	- 40	+ 110	15
	3310/5	5/8"				1,26					
	3310/M12S	-	1/2"	12		0,7					
	3310/4S			-		1,26					8
	3310/5S			16		1,26					
	3310/7S			22		1,84					

(1): in conformità a omologazione UL

(1): according to UL approval

(1): conformément à homologation UL

(1): Übereinstimmung zur UL-Zulassung